



≡ TDSB150

(2) 200W SOLAR PANEL PROVIDES A CHARGE FOR THE 150AH BATTERIES

Power generation:	200W max
-------------------	----------

Power generation voltage:	16(V) max
---------------------------	-----------

Power generation current:	12.5(A) max
---------------------------	-------------

Battery capacity:	12V.150AH
-------------------	-----------

Power status display:	Digital voltage display
-----------------------	-------------------------

Charge/discharge protection current:	20A
--------------------------------------	-----

Short circuit protection current:	20A
-----------------------------------	-----

Overcharge protection voltage:	12.6V
--------------------------------	-------

Over discharge protection voltage:	9.6V
------------------------------------	------

External charging power supply:	12.6V5A
---------------------------------	---------

Full charge life:	within 30W about 150AH≤96H
-------------------	----------------------------

Panel size	26.3"x35.4" per panel
------------	-----------------------

Weight:	68.3lb
---------	--------



1. MCU control, standby ultra-low power consumption;
2. The charging principle adopts a three-stage charging algorithm to charge the battery once a week, which can effectively prevent the battery from being unbalanced and vulcanized, and increase the battery life;
3. The power MOSFET is used as an electronic switch without any mechanical switch and without any protective action delay;
4. Charge and discharge green and red LED indicator, discharge light control + timing, pure light control, normally open mode can be manually adjusted



Charging Mode:	PWM mode
System Current:	3A
System Voltage:	7.4V, 11.1V, 14.8V
Power Input:	$\leq 18W$, $\leq 18W$, $\leq 36W$
Input withstand voltage:	$\leq 25V$
Overload protection/ Short circuit:	1.5 times rated current delay for 5 minutes off,
Protection:	Automatic recovery after 5 minutes; ≥ 3 times rated current short circuit protection action
Charge loop drop:	$\leq 0.7V$
Discharge circuit voltage drop:	$\leq 0.1V$
Overvoltage protection voltage:	5.5 (3.7V), 9.4 (7.4V), 13.6 (11.1V), 17.8 (14.8V)
Overvoltage recovery voltage:	5.0 (3.7V), 8.9(7.4V). 13.1 (11.1V), 17.3 (14.8V)
Charge cut-off Voltage:	4.2 (3.7V), 8.4(7.4V), 12.6 (11.1V), 16.8 (14.8V)
Over-discharge protection Voltage:	3.2 (3.7V), 6.0(7.4V), 9.0 (11.1V), 12.0 (14.8V)
Over-Discharge Recovery Voltage:	3.7 (3.7V), 7.4(7.4V), 11.1 (11.1V), 14.8 (14.8V)
Charging Return Voltage:	3.7 (3.7V), 7.4(7.4V), 11.1 (11.1V), 14.8 (14.8V)
Daytime identification voltage:	3.0 (3.7V), 3.5 (7.4V), 7 (11.1V/14.8V)
Night identifying voltage:	1.0 (3.7 V), 1.5 (7.4V), 3 (11.1V/14.8V)

Operation Temperature:	-86°F~+131°F
Storage Temperature:	-113°F~+158°F
Operating Relative Humidity:	$\leq 90\%RH$, no condensation
IP Grade:	IP30
External Dimensions:	2.1*2.7*.86 inch
Installation Cabling:	AWG22~14/2mm ²
Weight:	70.54 lb